

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard
 29 CFR 191-1200. Standard must be
 consulted for specific requirements

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List) MOXIE SEALER 1400	Note Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
---	--

Section I	
Manufacturer's Name The MOXIE International, Inc.	Emergency Telephone Number 916-338-3393 or 916-332-6272
Address (Number, Street, City, State, and ZIP code) 5710-B Roseville Road Sacramento, CA 95842	Telephone Number for Information 916-338-3393 Date Prepared 6-16-99

Section II ☉ Hazardous ingredients/identity information				
Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Hazardous Components: NONE	NONE	NONE	NONE	NONE
Chemical Name: Sodium Siliconate, water, proprietary formulation				
Product contains no ingredients subject to DOT, EPA, CERCLA/SARA environmental release report regulations.				

Section III ☉ Physical/Chemical Characteristics			
Boiling Point	212°F	Specific Gravity (H ₂ O = 1)	1.02
Vapor Pressure (mm Hg.)	Less Than 20	Melting Point	Less than 10
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	1
Solubility in Water 100%			
Appearance and Odor Clear; water white to light straw			

Section IV ☉ Fire and Explosion Hazard Data			
Flash Point (Method Used) NONE	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media None required; product is non-combustible. In areas where product is stored, can use water, dry-chemical, CO ₂ , foam.			
Special Fire Fighting Procedures NONE			
Unusual Fire and Explosion Hazards NONE			

(Reproduce Locally)
 OSHA 174 Sept 1965

MOXIE Sealer 1400

Section V Ⓞ Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	N/A

Incompatibility (*Materials to Avoid*)

The Product is Alkaline; avoid contact with acids

Hazardous Decomposition or Byproducts

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will not Occur	X	N/A

Section VI Ⓞ Health Hazard Data

Route(s) of Entry	Inhalation?	Skin?	Ingestion?
	X	N/A	X

Health Hazards (*Acute and Chronic*)

May cause skin irritation

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Signs and Symptoms of Exposure

May irritate eyes, Prolonged exposure may irritate skin.

Medical Conditions

Generally Aggravated by Exposure None

Emergency and First Aid Procedures

In case of contact with eyes, Flush with plenty of water for at least 15 minutes.

Section VII Ⓞ Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Mop from surface or flush with water to drain, (will not harm/corrode drains; will benefit concrete/masonry)

Waste Disposal Method

Flush to Drain

Precautions to be Taken in Handling and Storing

Keep from freezing. Store above 40⁰ degrees F.

Other Precautions

Section VIII Ⓞ Control Measures

Respiratory Protection (*Specify Type*)

Not required

Ventilation	Local Exhaust	Special
	N/A	N/A
	Mechanical	Other
	N/A	N/A

Protective Gloves	Eye Protection
Rubber	Face shield or goggles

Other Protective Clothing or Equipment

Clothing which will protect skin from contact.

Work/Hygienic Practices

Maintain clean environment with any spills removed