

**Material Safety Data Sheet**

May be used to comply with  
 OSHA's Hazard Communication Standard  
 29 CFR 191-1200. Standard must be  
 consulted for specific requirements

**U.S. Department of Labor**

Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072



<b>IDENTITY (As Used on Label and List)</b> MOXIE FLOORING SEALANT II (MFSII)	<i>Note</i> Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

<b>Section I</b>	
Manufacturer's Name The MOXIE International, Inc.	Emergency Telephone Number 916-338-3393 or 916-332-6272
Address (Number, Street, City, State, and ZIP code) 5710-B Roseville Road  Sacramento, CA 95842	Telephone Number for Information 916-338-3393  Date Prepared 6-16-99

<b>Section II ☉ Hazardous ingredients/identity information</b>				
Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Hazardous Components: NONE	NONE	NONE	NONE	NONE
Chemical Name: Inorganic, chemically reactive, complex catalyzed, hydrous silicate solution, proprietary formulation				
Product contains no ingredients subject to DOT, EPA, CERCLA/SARA environmental release report regulations.				
VOC=0				

<b>Section III ☉ Physical/Chemical Characteristics</b>			
Boiling Point	N/D	Specific Gravity (H <sub>2</sub> O = 1)	1.11
Vapor Pressure (mm Hg.)	N/D	Melting Point	Less than 10
Vapor Density (AIR = 1)	N/D	Evaporation Rate (Butyl Acetate = 1)	1
Solubility in Water 100%			
Appearance and Odor Clear; water white to light straw			

<b>Section IV ☉ Fire and Explosion Hazard Data</b>			
Flash Point ( Method Used) NONE	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media None required; product is non-combustible. In areas where product is stored, can use water, dry-chemical, CO <sub>2</sub> , foam.			
Special Fire Fighting Procedures NONE			
Unusual Fire and Explosion Hazards NONE			

(Reproduce Locally)  
 OSHA 174 Sept 1965

**MOXIE FLOORING SEALANT II (MFSII)**

**Section V Ⓢ Reactivity Data**

Stability	Unstable		Conditions to Avoid
	Stable	X	N/A

Incompatibility (*Materials to Avoid*)  
The Product is Alkaline; avoid contact with acids

**Hazardous Decomposition or Byproducts**

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will not Occur	X	N/A

**Section VI Ⓢ Health Hazard Data**

Route(s) of Entry	Inhalation?	Skin?	Ingestion?
	X	N/A	X

Health Hazards (*Acute and Chronic*)  
May cause skin irritation

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Signs and Symptoms of Exposure  
May irritate eyes, Prolonged exposure may irritate skin.

Medical Conditions  
Generally Aggravated by Exposure  
None

Emergency and First Aid Procedures  
In case of contact with eyes, Flush with plenty of water for at least 15 minutes.

**Section VII Ⓢ Precautions for Safe Handling and Use**

Steps to be Taken in Case Material is Released or Spilled  
Mop from surface or flush with water to drain, (will not harm/corrode drains; will benefit concrete/masonry)

Waste Disposal Method  
Flush to Drain

Precautions to be Taken in Handling and Storing  
Keep from freezing. Must be discarded if frozen. Store above 40 degrees F.

Other Precautions

**Section VIII Ⓢ Control Measures**

Respiratory Protection (*Specify Type*)  
Not required

Ventilation	Local Exhaust	Special
	Mechanical	Other
	N/A	N/A
	N/A	N/A

Protective Gloves  
Rubber

Eye Protection  
Face shield or goggles

Other Protective Clothing or Equipment  
Clothing which will protect skin from contact.

Work/Hygienic Practices  
Maintain clean environment with any spills removed